

PRODUCT SPECIFICATIONS FOR CS74B

WEIGHTS

| | |
|------------------------------------|----------|
| Operating Weight - With Cab | 16000 kg |
|------------------------------------|----------|

| | |
|-------------------------------|----------|
| Weight - Drum with Cab | 10620 kg |
|-------------------------------|----------|

OPERATING SPECIFICATIONS

| | |
|-------------------------|---------|
| Compaction Width | 2134 mm |
|-------------------------|---------|

| | |
|--|--------|
| Turning Radius - Inside Drum Edge | 3.68 m |
|--|--------|

| | |
|-------------------------|--------|
| Ground Clearance | 437 mm |
|-------------------------|--------|

| | |
|--------------------------------------|------------|
| Static Linear Load - With Cab | 49.7 kg/cm |
|--------------------------------------|------------|

| | |
|-------------------------------|-----------|
| Travel Speed - Maximum | 11.4 km/h |
|-------------------------------|-----------|

ENGINE

| | |
|--------------------|----------|
| Gross Power | 129.5 kW |
|--------------------|----------|

| | |
|---------------------|---------------------|
| Engine Model | Cat C4.4 with ACERT |
|---------------------|---------------------|

DIMENSIONS

| | |
|---------------------------------------|--------|
| Height - With ROPS/FOPS or Cab | 3.11 m |
|---------------------------------------|--------|

| | |
|-----------------------|--------|
| Overall Length | 6.05 m |
|-----------------------|--------|

| | |
|----------------------|--------|
| Overall Width | 2.33 m |
|----------------------|--------|

| | |
|----------------------|---------|
| Drum Diameter | 1534 mm |
|----------------------|---------|

| | |
|--|-------|
| Overall Width - With Blade Option | 2.5 m |
|--|-------|

| | |
|-------------------|---------|
| Drum Width | 2134 mm |
|-------------------|---------|

| | |
|---|--------|
| Wheel Base | 2.9 m |
| Overall Length - With Blade Option | 6.55 m |
| Optional Blade Height | 688 mm |

VIBRATORY SYSTEM

| | |
|--|------------------------------|
| Centrifugal Force - Maximum | 332 kN |
| Nominal Amplitude - Low | 0.98 mm |
| Centrifugal Force - Minimum | 166 kN |
| Vibratory Frequency - Standard | 28 Hz (1680 vpm) |
| Nominal Amplitude - High | 2.1 mm |
| Variable Frequency Option Range | 23.3 - 28 Hz (1400-1680 vpm) |

TIRES

| | |
|--------------|-----------|
| Tires | 23.1 x 26 |
|--------------|-----------|

SERVICE REFILL CAPACITIES

| | |
|---------------------------|-------|
| Fuel Tank Capacity | 332 l |
|---------------------------|-------|
